



# SCHUMACHER ELEVATOR COMPANY

## REQUEST FOR QUOTATION

\*\* PLEASE SEND SPECIFICATION IF AVAILABLE \*\*

**COMPANY:** \_\_\_\_\_

**TODAY'S DATE:** \_\_\_\_\_ **BID DATE:** \_\_\_\_\_

**CONTACT:** \_\_\_\_\_

**PROJECT NAME:** \_\_\_\_\_

**TELEPHONE:** \_\_\_\_\_

**PROJECT LOCATION:** \_\_\_\_\_

**FAX:** \_\_\_\_\_

**APPLICABLE ANSI A17.1 CODE YEAR:** \_\_\_\_\_

*Schumacher will not quote without applicable code year provided*

**E-MAIL:** \_\_\_\_\_

**ELEVATOR TYPE:**

HYDRAULIC	TRACTION	
In Ground	Geared	Passenger
Holeless	Gearless	Freight
Roped	Overhead	
LULA	Basement	
Residential:	MRL	
7000	9000	

**QUANTITY:** \_\_\_\_\_ **CAPACITY:** \_\_\_\_\_ lbs.

**SPEED:** \_\_\_\_\_ fpm **TRAVEL:** \_\_\_\_\_

**LANDINGS:** Quantity: \_\_\_\_\_  
 \_\_\_ Front \_\_\_ Rear \_\_\_ Side

**MACHINE ROOM:** Adjacent Remote \_\_\_\_\_ Feet

**POWER SUPPLY:** \_\_\_\_\_ Volts \_\_\_\_\_ Phase  
*(Must have 3 phase for speeds higher than 30 fpm)*

**HOISTWAY SIZE:** \_\_\_\_\_ Width x \_\_\_\_\_ Depth

Overhead: \_\_\_\_\_ (under hoistbeam) Pit Depth: \_\_\_\_\_

**HOISTWAY CONSTRUCTION:** Wall Thickness: \_\_\_\_\_  
 CMU (Concrete) Drywall

**CAB:** \_\_\_\_\_ Height  
 600 (Steel with painted walls)  
 700 (Wood with plastic laminate)  
 800 (Steel with off-set panels)  
 850 (Top: vertical laminate offset panels; Bottom: SST panels )  
 900 (Steel, glass, custom finishes)

**LIGHTING:** Fluorescent Incandescent LED

**CEILING:** Translucent Panels Egg Crate Stainless Steel

**CAR DOOR:** Stainless Steel Baked Enamel  
 Plastic Laminate Other: \_\_\_\_\_

**FAN:** 1-speed 2-speed Other: \_\_\_\_\_

**HANDRAILS:** Flat Bar Round Quantity: \_\_\_\_\_ Size: \_\_\_\_\_

Bumper Rails: Wood Steel Quantity: \_\_\_\_\_ Size: \_\_\_\_\_

Pads and Hooks

Side Walls Rear Wall

**HYDRAULIC POWER UNIT:** Submersible Dry  
 Tank Heater Tank Cooler

**TRACTION DRIVE:** VVVF AC DC

**CONTROLLER:** Schumacher Controller  
 Other: \_\_\_\_\_

**CONTROLLER OPTIONS:**  
 Battery Lowering Emergency Power Provision  
 Fire Phase I & II Load Weighing  
 Seismic Package Zone: \_\_\_\_\_

**GUIDE SHOES:** Roller Slide Slide Guide Lubricators

**FIXTURES:** Standard Schumacher Other: \_\_\_\_\_

Main Car Station Auxiliary Car Station Pre-wire  
 Hall Lanterns Car Riding Lantern  
 Hall PI: Digital Multi-light Quantity: \_\_\_\_\_  
 Car PI: Digital Multi-light Quantity: \_\_\_\_\_

Vandal Resistant Surface Mount Hall Fixtures  
 Keyed Hall Stations ADA Compliant Telephone  
 110-Volt Duplex Outlet Engraving  
 Firemen Phone Jack Firemen Service Key Station  
 Load Weighing Indicator Lobby Panel  
 Service Cabinet (in car) Fire Control Panel  
 Hoistway Access System Remote: \_\_\_\_\_ Feet  
 Outside Alarm Bell O & M Manuals - Quantity: \_\_\_\_\_

**RETURN:** Swing Stationary Recessed (Freight Only)

**ENTRANCES:** \_\_\_\_\_ Width x \_\_\_\_\_ Height  
 Finish: #4 Stainless Steel Baked Enamel Prime  
 Other: \_\_\_\_\_

**DOOR TYPE:** Single Slide Two Speed Center Opening

**SILL ANGLES:** Integral Structural  
 Finish: Aluminum Nickel Silver Other: \_\_\_\_\_

**FREIGHT DOOR:** Power Manual  
 Finish: Stainless Steel Baked Enamel Prime

**DOOR OPERATOR:** GAL-MOVFR (Standard) Pre-wire  
 Other: \_\_\_\_\_

**ADDITIONAL FEATURES:**

\_\_\_\_\_